BESTIE



H20

Pewter

Onyx





Specifications:

Content: 100% Polyurethane

Backing: 89% Polyester, 11% Rayon

Finish: N/A

Direction: Up the Roll

Weight: 24.4 oz. / lin. yd.

Width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013 **UFAC Class 1**

Performance:

Abrasion: Heavy Duty - Exceeds 185,000 cycles

(Wyzenbeek – Cotton Duck Abradant) (ASTM D4157)

Light Fastness: Class 4/200 hrs. min. (AATCC16A)

Color Fastness: Class 4 (ASTM D3597, AATCC 8) Wet Class 4 (ASTM D3597, AATCC 8) Dry

Physical Properties: 117 lbs. warp, 120 lbs. weft (ASTM D5034) Breaking

67 lbs. warp, 49 lbs. weft (ASTM D4034) Seam Slippage

50,000 cycles (CFFA 10) Flex Resistance

Pass (CFFA 6a) Cold Crack Pass (ISO 1419) 10 weeks

Made In: China

Care & Cleanability:

Cleaning code W - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam-to-seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).

Culp Hospitality 1823 Eastchester Drive High Point, NC 27265 Contact: hospitality@culp.com www.culphospitality.com