DILLON



Pattern Detail and Specifications



Specifications:

Content: 100% Polyurethane

Backing: 89% Polyester, 11% Rayon

Finish: Antimicrobial

Repeat: N/A

Weight: 27.2 oz. / lin. yd.

Width: 54 inches

Flammability Passes:

California Tech. Bulletin #117-2013 UFAC Class 1 NFPA 260 Class 1

Performance:

Abrasion: Heavy Duty – Exceeds 200,000 cycles

(Wyzenbeek - Cotton Duck Abradant) (ASTM D4157)

Light Fastness: Class 4/200 hrs. min. (AATCC16A)
Color Fastness: Class 4 (ASTM D3597, AATCC 8) Wet

Class 4 (ASTM D3597, AATCC 8) Dry

Physical Properties: 50,000 Cycles (CFFA 10) Flex Resistance

130 lbs. warp, 113 lbs. weft (ASTM D5034) Breaking

Strength

47 lbs. warp, 55 lbs. weft (ASTM D4034) Seam Slippage

Pass (CFFA 6a) Cold Crack Pass (ISO 1419) 5 weeks

Recommended Use: Upholstery Made In: China

Care & Cleanability:

Cleaning code **W** - Spot clean only with water-based upholstery shampoo or foam upholstery cleaner. Pretest a small, inconspicuous area before proceeding. Do not over wet. Do not use solvents to spot clean. Cushion covers should not be removed and laundered. When cleaning a spill, blot immediately to remove the spilled material. Evenly clean the entire panel in a seam-to-seam fashion. Do not clean just the spots or stains. When an overall soiled condition has been reached and professional care is required, contact an IICRC certified firm (www.iicrc.org).

Culp Hospitality 1823 Eastchester Drive High Point, NC 27265 Contact: hospitality@culp.com www.culphospitality.com