



HATHAWAY




Desert



White




Smoky




Raspberry




Fire




Maroon



Onyx




Fog




Nickel



Cafe




Root Beer




Navy



Electric Blue



Ocean




Aqua




Lemon



Tangerine



Apple



Grape

Pattern Detail and Specifications

Specifications:

Content:	82% PVC Vinyl, 18% Polyester
Backing:	82% PVC Vinyl, 18% Polyester
Finish:	Antimicrobial
Direction:	Up the Roll
Weight:	42.2 oz. / lin. yd.
Width:	54 inches

Flammability Passes:

California Tech. Bulletin #117-2013  
UFAC Class 1  
NFPA 260 Class 1

Performance:

Abrasion:	Heavy Duty – Exceeds 100,000 cycles (Wyzenbeek – Cotton Duck Abradant) (ASTM D4157)
Light Fastness:	Class 4/200 hrs. min. (AATCC16A)
Color Fastness:	Class 4 (ASTM D3597, AATCC 8) Wet Class 4 (ASTM D3597, AATCC 8) Dry
Physical Properties:	106 lbs. warp, 110 lbs. weft (ASTM D5034) Breaking Strength 44 lbs. warp, 53 lbs. weft (ASTM D4034) Seam Slippage
Made In:	China

Care & Cleanability:

A clean cloth, dampened with the appropriate cleaning solution, should be applied to the affected areas as soon as possible. Blot the fabric with the treated cloth, working from outer edge of the stained area and moving in toward the center. In order to effectively out the stain, renew the cleaning cloth as often as necessary to maintain an absorbent surface.

Clean all stained areas as soon as possible in accordance with the recommended stain removal procedures. Spot clean with upholstery shampoo, foam from a mild detergent, mild dry-cleaning solvent. Hot water extraction or steam cleaning is not a recommended cleaning method. Clean spots or stains from the outside to the middle of the affected area to prevent circling (see Stain Removal Matrix below).

1. Soap and water
2. Difficult stains use Fantastik® or Formula 409®
3. Disinfects with 5:1 water / bleach solution